



Solid-Finish Wood Ceiling Tiles



Organic-Texture Wood Ceiling Tiles

- Made from recycled, renewable material
- Up to 0.80 NRC
- Class 1 fire-rated
- Two distinctive styles
 - BIOLINE Solid-Finish
 - BIOLINE Organic-Texture

3800 Washington Avenue North
Minneapolis, MN 55412
Toll-Free 1-800-662-0032
sales@illbruck-acoustic.com
www.illbruck-acoustic.com

BIOLINE™ Wood Ceiling Tiles

Product Information

illbruck's BIOLINE Wood Ceiling Tiles add warmth and elegance to any décor. They are available in two distinctive styles and are made from recycled, renewable materials. The Solid-Finish tiles provide the beauty of real wood veneer while the organic tiles offer a unique fiber texture.

Environmentally friendly, BIOLINE Solid-Finish tiles contain 70 percent recycled material. Choose from custom or standard natural wood veneers including cherry, beech or maple in perforated or unperforated options.

BIOLINE Organic-Texture tiles reduce reverberation and echo by absorbing between 55 and 80 percent of the sound directed toward them. Made from 80 percent recycled material, Organic-Texture tiles are offered in custom or three standard wood shades of light, medium and dark to complement your décor.

Applications

- Offices and conference rooms
- Showrooms and training areas
- Entries and boardrooms
- Entertainment facilities
- Religious facilities

BIOLINE Wood Ceiling Tile features

- Rigid, durable, stable material that tolerates a broad range of jobsite environmental conditions
- Urea-formaldehyde-free core
- Standard finish: certified green, UV-cured, waterborne-finish with UV blockers for color stability
- Excellent impact resistance
- Fits illbruck's or other conventional grid systems
- Field machinable, custom cuts and cutouts offered



Solid-Finish Wood Ceiling Tiles



Cherry



Perforated Beech



Perforated Maple

Organic-Texture Wood Ceiling Tiles



Offered in light, medium and dark (medium shown)

Solid-Finish

- 70 percent recycled, post-industrial material (by weight)
- Perforated patterns available in rectangular and diamond
- Perforated holes available in 0.25" and 0.31" (6.4 mm and 8 mm) and custom diameters
- Coordinated core color and veneer; no edge banding required
- Class 1 fire-rated
- Three standard natural wood veneers and custom-tinted veneer
- Two-year limited warranty against veneer delamination
- Self-centering revealed edge

Organic-Texture

- 80 percent recycled, post-industrial material (by weight)
- Noise reduction coefficient (NRC) of 0.55 and 0.65* (ASTM C423 E-mount)
- Noise reduction coefficient (NRC) of 0.80* (ASTM C423 modified A-mount)
- Three standard wood shades of light, medium and dark or custom shades
- Class 1 fire-rated (ASTM E84); flame spread: 25; smoke density: 70
- Self-centering, high-strength, molded revealed edge

Style	Profile	Dimensions	Recycled Content**	NRC
Solid-Finish	Self-centering revealed edge	24" x 24", 24" x 48" or custom	70%	N/A
Solid-Finish Perforated	Self-centering revealed edge	24" x 24", 24" x 48" or custom	70%	0.40
Organic-Texture	Self-centering revealed edge	24" x 24", 24" x 48" 48" x 72" or custom	80%	0.55, 0.65* and 0.80*

*Using willtec® acoustical foam or fiberglass backer.

**By weight

As with all natural products, colors will vary.

Due to limitations of the printing process, the colors to the left may not be accurate.

Other Products

illbruck acoustic, inc. manufactures a range of attractive acoustic ceiling tiles, wall panels and baffles for commercial and industrial applications, including:

CONTOUR® Ceiling Tiles

SQUARELINE® Metal Ceiling Tiles

HARMONI™ Ceiling Tiles

WHITELINE® Ceiling Tiles

illbruck Ceiling Grid Systems

SONEX® Baffles and Panels

FABRITEC™ Panels

PROSPEC® Barriers, Foams and Composites